TOPIC

Engineering Probability and Statistics – Section II – Question 9

QUESTION

Two types of plastic are suitable for use in an electronics component manufacturer. The breaking strength of this plastic is important. It is known that $\sigma_1 = 2$ psi and $\sigma_2 = 3$ psi. For a random sample of size $n_1 = 10$ and $n_2 = 13$, we obtain $\bar{x}_1 = 156$ psi, and $\bar{x}_2 = 163$ psi. The company will not adopt plastic 2 unless $\mu_2 - \mu_1 > 5$ psi. Consider the hypothesis test μ_0 : $\mu_2 - \mu_1 = 5$ versus μ_1 : $\mu_2 - \mu_1 > 5$. The P-value of this test most nearly is

- (A) 0.010
- (B) 0.028
- (C) 0.053
- (D) 0.086

HINT

Since both variances are known, this is a z test. Then the P-value for hypothesis test H₀: $\mu_2 - \mu_1 = \mu_0$ versus H₁: $\mu_2 - \mu_1 > \mu_0$ is $1 - \Phi(z_0)$, where

$$z_0 = \frac{\bar{x}_2 - \bar{x}_1 - \Delta_0}{\sqrt{\frac{\sigma_2^2 + \sigma_1^2}{n_2 + n_2}}}$$

CONTRIBUTOR

Michael Weng